



አባይ ኮንስትራክሽን ኃ/የተ/የግል/ማህበር
Abay Construction PLC

የፓምፕ፣ ጀነሬተር፣ ኤችዲፒ ፓይፕ፣ የውሃ እቃዎች እና የውሃ ቦቴ ኪራይ
አገልግሎት ግዥ ብሄራዊ ግልፅ ጨረታ ሰነድ

ጥቅምት/2017 ዓ.ም

ፓምፕ፣ ጀነሬተር፣ ኤችዲፒ ፓይፕ እና የውሃ እቃዎች ግዥ ብሄራዊ ግልፅ የጨረታ ማስታወቂያ

የጨረታ ቁጥር አኮኃ/ብግጨ/005/17

አባይ ኮንስትራክሽን ኃ/የተ/የግ/ማህበር ለተለያዩ ፕሮጀክቶች አገልግሎት የሚወልድ ፓምፕ፣ ጀነሬተር፣ ኤችዲፒ ፓይፕ እና የውሃ እቃዎች ግዥ እና የነዳጅ ቦቱ ትራንስፖርት አገልግሎት ኪራይ ግዥ በብሔራዊ ግልጽ ጨረታ አወዳድሮ መግዛት ይፈልጋል።

ስለሆነም ድርጅቱ የሚከተሉትን መስፈርቶች የሚያሟሉ ተጫራቾችን ይጋብዛል።

1. በዘመኑ የታደሰ ህጋዊ የንግድ ስራ ፈቃድ፣ የግብር ከፋይ መለያ ቁጥር፣ የቫት ምዝገባ የምስክር ወረቀት ፎቶ ኮፒ ከመጫረቻ ሰነዶቻቸው ጋር አያይዘው ማቅረብ የሚችሉ፤
2. የሚገዙ ዕቃዎች ዓይነትና ዝርዝር መግለጫ ከጨረታ ሰነዱ ማግኘት ይቻላል።
3. ተጫራቾች የጨረታ ሰነዱን አማራ ክልል ባህርዳር ከተማ ቀበሌ 16 ህዳሴ ሰፈር ፊት ለፊት አመልድ ጋራጅ ወስጥ ከሚገኘው አባይ ኮንስትራክሽን ኃ/የተ/የግ/ማህበር ቢሮ ከግዥ የሥራ ሂደት ቢሮ ቁጥር 19 የማይመለስ ብር 200 /ሁለት መቶ ብር/ በመክፈል ማግኘት ይቻላል።
4. ተጫራቾች ለሚወዳደሩባቸው ዕቃዎች 2% የጨረታ ማስከበሪያ ዋስትና (Bid Bond) በባንክ በተረጋገጠ ትዕዛዝ (CPO) ወይም በሁኔታ ላይ ያልተመሰረተ የባንክ ዋስትና (Unconditional Bank Guarantee) በአባይ ኮንስትራክሽን ኃ/የተ/የግ/ማህበር ስም በማሳራት ማስያዝ አለባቸው።
5. ተጫራቾች በጨረታ ሰነዱ ላይ በተገለጸው መሰረት የጨረታውን ሰነድ በታሽገ ፖስታ ትክክለኛ ስምና አድራሻ በመጻፍ ይህ ማስታወቂያ ከወጣበት ቀን ጀምሮ ለ15 ተከታታይ ቀናት እስከ 15ኛው ቀን 8:00 ሰዓት በስራ ሰዓት ከግዥ የስራ ሂደት ቢሮ ቁጥር 19 በተዘጋጀው የጨረታ ሳጥን ማስገባት ይችላሉ።
6. ጨረታው አየር ላይ ከዋለበት ቀን ጀምሮ በ15ኛው ተከታታይ ቀን ከቀኑ በ8:00 ሰዓት ይዘጋል፤ 15 ተከታታይ ቀን ከቀኑ 8:30 ሰዓት ተጫራቾች ወይም ህጋዊ ወኪሎቻቸው በተገኙበት በግዥ የስራ ሂደት ቢሮ ቁጥር 19 ይከፈታል።
7. 15ኛው ተከታታይ ቀን የበዓላት ቀን ከሆነ ጨረታው በሚቀጥለው የስራ ቀን የሚከፈት ይሆናል።
8. ድርጅቱ የተሻለ አማራጭ ካገኘ ጨረታውን በክፍልም ሆነ በሙሉ የመሰረዘ መብቱ የተጠበቀ ነው።
9. በጨረታው ለመሳተፍ ለሚፈልጉ ስለጨረታው ዝርዝር መረጃ ከግዥ የስራ ሂደት ቢሮ ቁጥር 19 ድረስ በአካል በመገኘት ወይም በስልክ ቁጥር 09 91 02 14 30 በመደወል ወይም በድረገጻችን <https://www.abayconstruction.org.et/auction-bid/> ላይ ማግኘት ይችላሉ።

አባይ ኮንስትራክሽን ኃ/የተ/የግ/ማህበር



ይዘት
ገጽ

የተጫራቾች መመሪያ 4

1. ጠቅላላ 4

2. የጨረታ ሰነድ ስለማሻሻል 4

3.	የጨረታ ማስከበሪያ ዋስትና /Bid Bond/ እና የውል ማስከበሪያ.....	5
4.	የመጫረቻ ሰነድ አቀራረብ እና የውድድር ሁኔታ	5
5.	የመጫረቻ ሰነድ ማቅረቢያ የጊዜ ገደብ	6
6.	ራስን ከጨረታ ስለማግለል	6
7.	ጨረታ መክፈት፣ መገምገምና አሸናፊ መለየት.....	6
8.	ጨረታን ውድቅ ስለማድረግ	7
9.	የመጫረቻ ሰነድ ጸንቶ የሚቆይበት ጊዜ	7
10.	የጨረታ ውጤትን ስለመግለጽና የውል ስምምነት ስለመግባት	7
11.	የማቅረቢያ ቦታ	8
12.	የውል ማስከበሪያ	8
13.	የአቅርቦት መጠን	8
14.	አቤቱታ ስለማቅረብ.....	8

የተጫራቾች መመሪያ

1. ጠቅላላ

- 1.1. የግዥ ፈጻሚው መ/ቤት ሙሉ አድራሻ አማራ ክልል ባህር ዳር ከተማ ቀበሌ 16 ህዳሴ ሰፈር ፊት ለፊት አመልድ ጋራጅ ዉስጥ ነው።
- 1.2. ግዥ ፈጻሚው መ/ቤት የሚገዛቸው ዕቃዎች ፓምፕ፣ ጀነራተር፣ ኤችዲፒ ፓይፕ፣ የዉሃ እቃዎች እና የዉሃ ቦቴ ኪራይ አገልግሎት ግዥ ናቸው።
- 1.3. **ተጫራቾች ከመጫረቻ ሰነዳቸው ጋር የታደሰ የንግድ ስራ ፈቃድ፣ የግብር ከፋይ መለያ ቁጥር /TIN/፣ የተጨማሪ እሴት ታክስ /VAT/ ከፋይነት የምስክር ወረቀት ማቅረብ አለባቸው።**
- 1.4. በጨረታው ለመሳተፍ የሚፈልጉ ተጫራቾች የጨረታ ሰነዱን ከድርጅቱ ግዥ የስራ ሂደት ቢሮ ቁጥር 19 የማይመለስ ብር 200 (ሁለት መቶ ብር) በመክፈል የጨረታው ማስታወቂያ ከወጣበት ቀን ጀምሮ እስከሚዘጋበት ቀን ድረስ ዘወትር በሥራ ሰዓት መውሰድ ይችላሉ።
- 1.5. ተጫራቾች የሚያቀርቡት ዋጋ ማንኛውንም ዓይነት ግብር የሸፈነ መሆን አለበት።
- 1.6. ድርጅቱ (ግዥ ፈጻሚው) ከከፍተኛው ላይ የሚቀንሰው 2% ዊዝሆልድ ታክስ ብቻ ነው።
- 1.7. ተጫራቾች በወጣው የጨረታ ሰነድ ላይ ጥያቄ ወይም ማብራሪያ ከፈለጉ በስልክ ቁጥር 0991021430 በመደወል ወይም በጽሁፍ ጨረታው ከወጣበት ቀን ጀምሮ እስከ **10ኛው** ቀን ማቅረብ አለባቸው። ግዥ ፈጻሚውም እስከ **15ኛው** ቀን ማብራሪያ ይሰጣል።
- 1.8. ተጫራቾች በሚያቀርቡት የመወዳደሪያ ሀሳብ ሠነድ ላይ ሙሉ ስማቸውን የስልክ፣ የፋክስና የመልዕክት ሣጥን ቁጥራቸውን መጻፍ ይኖርባቸዋል።
- 1.9. ዋጋ የሚሞሉት በድርጅቱ በተዘጋጀው ቅጽ ብቻ መሆን ይኖርበታል። ይሁን እንጂ በራሳቸው የዋጋ ማቅረቢያ ቅጽ ለመጠቀም የሚፈልጉ ተጫራቾች ካሉ ከድርጅቱ በተሰጣቸው የዋጋ ማቅረቢያ ቅጽ ላይ የተመለከቱትን በጥንቃቄ ወደ ራሳቸው ቅጽ ማስፈር አለባቸው። በዚህ ወቅት የመረጃ መዘለል ቢፈጠር የተጫራቾች ሰነድ ከውድድር ውጭ የሚደረግ መሆኑ በቅድሚያ ሊታወቅ ይገባል።
- 1.10. ድርጅቱ ጨረታውን ሙሉ በሙሉ ወይም በከፊል የመሠረዝ መብቱ የተጠበቀ ነው።

2. የጨረታ ሰነድ ስለማሻሻል

- 2.1. ድርጅቱ ጨረታው አየር ላይ ከዋለበት ቀን ጀምሮ እስከ **10ኛው** ቀን ድረስ በሥራ ሰዓት በራሱ ወይም የጨረታ ሰነዱን በገዙ እጩ ተወዳዳሪዎች በሚቀርቡ ጥያቄዎች መነሻነት የጨረታ ሰነዱን ማሻሻል ይችላል። **ከ10ኛው ቀን በኋላ ለቀረበ ማብራሪያ ወይም የማሻሻያ ጥያቄ ምላሽ እንዲሰጥ አይገደድም።**
- 2.2. የተደረገው ማሻሻያ የጨረታ ሰነዱ አካል የሚሆን ሲሆን በጽሁፍ ተዘጋጅቶ ሰነዱን ለገዙ እጩ ተወዳዳሪዎች እና በቀጣይ ሰነዱን ለሚገዙ ሁሉ በተገቢው ሁኔታ በእኩል ጊዜ እንዲደርስ ይደርጋል።
- 2.3. በጨረታ ሰነዱ ማሻሻያ መሠረትም ድርጅቱ የጨረታ መክፈቻ ጊዜውን እንደ አስፈላጊነቱ አስከ 5 ተከታታይ ቀናት ሊያራዝም ይችላል።



2.4. ተጫራቾች ቀደም ሲል ባስገቡት የጨረታ ዋጋ ላይ ማሻሻያ በማድረግ በልዩ ሁኔታ መቀነስ ቢፈልጉ ቅድመ ሁኔታ ባልተቀመጠበት አግባብ ካቀረቡት ዋጋ የሚቀንሱትን መጠን በመቶኛ (%) የጨረታው ሳጥን እስከሚዘጋበት ሰዓት ብቻ ፊርማና ማህተም ተደርጎበት ማስገባት ይችላሉ። ሆኖም የዋጋ ቅናሹ የግልጽ ጨረታ ሥርዓትን የማይጋፋ መሆን አለበት።

3. የጨረታ ማስከበሪያ ዋስትና /Bid Bond/ እና የውል ማስከበሪያ

3.1. ተጫራቾች ለሚወዳደሩበት የብር መጠን 2% የጨረታ ማስከበሪያ ዋስትና /bid bond/ በCPO ወይም በሁኔታ ላይ ያልተመሰረተ የባንክ ዋስትና (Unconditional Bank Guarantee) **ከዋጋ ማቅረቢያ (ከፋይናንሽያል ሰነድ) ጋር** በጥንቃቄ በታሸገ ፖስታ መቅረብ ይኖርበታል።

3.2. ከተጫራቾች የሚቀርበው የጨረታ ማስከበሪያ ዋስትና ፀንቶ መቆየ ጊዜ ጨረታው ከተከፈተበት ቀን ጀምሮ ቢያንስ ለ60 ቀናት ጸንቶ መቆየት ይኖርበታል።

3.3. ተሸናፊ ተጫራቾች ያስያዙትን የጨረታ ማስከበሪያ ዋስትና ጨረታው ተከፍቶ አሸናፊው ተለይቶና ውል ከተያዘ ጀምሮ ባሉት በ6 ወራት ውስጥ መውሰድ አለባቸው።

3.4. የጨረታ ማስከበሪያ ዋስትና በሚከተሉት ምክንያቶች በአንዱ ይወረሳል።

- ሀ. የጨረታ ማስከበሪያው ፀንቶ በሚቆይበት ጊዜ ውስጥ ተጫራቹ ራሱን ከውድድር ካገለለ፤
- ለ. አሸናፊው ተጫራቾች አሸናፊነቱ ከተገለጸበት በኋላ ውሉን ለመፈረም ፈቃደኛ ሆኖ ካልተገኘ፤
- ሐ. አሸናፊው እንዲያቀርብ የተጠየቀውን የውል ማስከበሪያ 10% ካላቀረበ፤
- መ. ተጫራቹ ጨረታውን ለማዛባት የሞከረ መሆኑ በማስረጃ ከተረጋገጠ፤



3.5. ከላይ በተ.ቁ 3.4 /ሀ-ሠ/ ከተመለከቱት አንዱን የፈፀመ ያስያዘው የጨረታ ማስከበሪያ ሙሉ ለሙሉ የሚወረስበት ሲሆን በህግም ሊጠየቅ ይችላል።

3.6. የውል ማስከበሪያ (performance bond) ለሸነፉበት ዕቃ 10% በCPO ወይም በሁኔታ ላይ ያልተመሰረተ የባንክ ዋስትና (Unconditional Bank Guarantee) ማቅረብ አለባቸው።

4. የመጫረቻ ሰነድ አቀራረብ እና የውድድር ሁኔታ

4.1. ተጫራቾች አስፈላጊ የሆኑ መረጃዎችን ፎቶ ኮፒ እና የሚያቀርቡትን የመጫረቻ ሰነድ በጨረታ ሰነዱ የተመለከተውን የዕቃ ዋጋ ማቅረቢያ ቅፅ በመጠቀም በተገለጸው ዝርዝር መግለጫ (Detail specification) መሠረት ፋይናንሽያል ሰነዳቸው እና ቴክኒካል ሰነዳቸው ስርዝ ድልዝ በሌለበት ሁኔታ በጥንቃቄና በዝርዝር በመሙላት በመፈረምና በእያንዳንዱ ገጽ ላይ ማህተም በማድረግ ማቅረብ ይጠበቅባቸዋል። ስርዝ ድልዝ ካለም ስለመስተካከሉ ፊርማቸውን በማስቀመጥ /ፖራፍ/ በማድረግ መረጋገጥ አለበት።

4.2. ተጫራቾች የመጫረቻ ሰነዳቸውን የሎት 01ን በሁለት ፖስታ ቴክኒካል እና ፋይናንሽያል ሰነድ የሚያቀርቡ ሲሆን በሌሎች ሎቶች ግን በአንድ ፖስታ ፋይናንሽያል የመጫረቻ ሰነድ ብቻ የሚያቀርቡ ይሆናል።

4.3. ውድድሩ በእያንዳንዱ ዕቃ ዝቅተኛ ዋጋ ያቀረበ አሸናፊ ይሆናል።

4.4. በማሸጊያ ፖስታ ላይ የሚከተሉትን ነጥቦች ማስፈር ያስፈልጋል።

- ሀ. የጨረታው ዓይነትና ቁጥር፤
- ለ. ጨረታውን ያወጣው መስሪያ ቤት ስምና አድራሻ፤
- ሐ. የተጫራቹ ስም፣ ስልክ ቁጥር፣ ፊርማና ሙሉ አድራሻ፤

4.5. በፖስታ የሚላክ የመጫረቻ ሰነድ በመዘግየቱና በጥንቃቄ ካለመታሸጉ ጋር በተያያዙ ችግሮች ግዥ ፈጻሚው መ/ቤት ኃላፊነቱን አይወስድም፡፡

5. የመጫረቻ ሰነድ ማቅረቢያ የጊዜ ገደብ

5.1 ተጫራቾች በጨረታ ሰነዱ ላይ ከተገለጸው የመጫረቻ ሰነድ ማስረከቢያ የመጨረሻ ቀንና ሰዓት በፊት የመጫረቻ ሰነዱን በተዘጋጀው የጨረታ ቦታ እና የጨረታ ሳጥን ውስጥ ማስገባት ይኖርባቸዋል፡፡ ሆኖም ተጫራቾች የመጫረቻ ሰነዶቻቸው ብዛት ያላቸው ከሆኑና በጨረታ ሳጥኑ ውስጥ ማስገባት አስቸጋሪ በሚሆንበት ጊዜ በድርጅቱ የግዥ የሥራ ሂደት ቢሮ ቁጥር 19 በመገኘት ለተመደበው ግዥ ኦፊሰር ማስረከብ ይችላሉ፡፡ ተረካቢውም የተጫራቹን ስምና አድራሻ እንዲሁም የተረከበበትን ቀንና ሰዓት በመመዝገብ ለመረከቡ ማረጋገጫ (ማስረጃ) የሚሰጥ ሲሆን በግዥ ኦፊሰር የተሰበሰቡ የመጫረቻ ሰነድ ፖስታዎችን ጨረታው ከመዘጋቱ 30 ደቂቃ በፊት ለግዥና ጨረታ ኮሚቴው ርክክብ ያደረጋል፡፡

5.2 በጨረታ ሰነዱ መሰረት የመጫረቻ ሰነድ ማስረከቢያ የመጨረሻ ቀንና ሰዓት ደርሶ የጨረታ ሳጥን ከተዘጋ በኋላ የሚቀርብ የመጫረቻ ሰነድ ተጫራቹ በአካል ከቀረበ በተጫራቹ እጅ እንዳለ በሌላ አግባብ የመጣ ከሆነም ሳይከፈት ለተጫራቹ /ለአቅራቢው/ ተመላሽ ይደረጋል፡፡

6. ራስን ከጨረታ ስለማግለል

6.1 ተጫራቾች የጨረታ ሳጥኑ ከመዘጋቱ ቀንና ሰዓት በፊት ራሳቸውን ከጨረታው ማግለል ይችላሉ፡፡ ስለሆነም ራሳቸውን ከጨረታው ስለማግለላቸው በሚያቀርቡት ሰነድ ላይ የድርጅቱ ህጋዊ ማህተም ማድረግና ሙሉ ስማቸውን መጻፍ ይኖርባቸዋል፡፡ የጨረታ ሰነዱን የሚሞሉና የሚፈረሙ ተወካዮች ከሆኑ ሕጋዊ የውክልና ማስረጃቸውን የተገናዘበ ፎቶ ኮፒ ከሚቀርበው ሰነድ ጋር በማያያዝ በፖስታ አሸገው የጨረታ ሳጥኑ ከመዘጋቱ በፊት በጨረታ ሳጥኑ ውስጥ ማስገባት ይኖርባቸዋል፡፡

6.2 የጨረታ መዝጊያ ጊዜ ከተጠናቀቀ በኋላ ተጫራቾች ባቀረቡት የመወዳደሪያ ሃሳብ ላይ ለውጥ ወይም ማሻሻያ ማድረግና ከጨረታው ራሳቸውን ማግለል አይችሉም፡፡

7. ጨረታ መክፈት፣ መገምገምና አሸናፊ መለየት

7.1. የጨረታው አየር ላይ ቆይታ 15 ተከታታይ ቀናት ሲሆን ጨረታው አየር ላይ ከዋለበት ቀን ጀምሮ በ15ኛው ቀን ከቀኑ 8:30 ሰዓት በድርጅቱ የግዥ የሰራ ሂደት ቢሮ ቁጥር 19 ተጫራቾች ወይም ህጋዊ ወኪሎቻቸው በተገኙበት በግልፅ ይከፈታል፡፡ ሆኖም ተጫራቾች ወይም ህጋዊ ወኪሎቻቸው ጨረታው በሚከፈትበት ቦታ፣ ቀንና ሰዓት በራሳቸው ምክንያት ባይገኙ ጨረታው እንዲከፈት በማድረግ ውድድሩ ይካሄዳል፡፡

7.2. ጨረታው ሲከፈት በንባብ የሚሰሙ የተጫራቾች ሥም፣ የተወዳደረበት ምድብ (ሎት)፣ የሚደረግ የዋጋ ቅናሽ ካለ መጠኑንና ሁኔታውን በሚመለከት (ቅድመ ሁኔታ ያልተቀመጠበት እና የጨረታ ሥርዓቱን የማይጋፋ መሆኑን)፣ የጨረታ ማስከበሪያ ዋስትና ዓይነትና መጠን እንዲሁም ሌሎች እጩ ተወዳዳሪዎች ደረጃቸውን ለማሳወቅ ይረዳቸዋል ተብለው የሚታሰቡ መሰረታዊ ነጥቦች በጨረታው መክፈቻ ወቅት ለተጫራቾች ይነበባሉ፡፡



- 7.3. በግዥ ፈጻሚ መ/ቤቱ የቀረቡትን የጨረታ ሰነዶች በመገምገም ሂደት አስፈላጊ ሆኖ ካገኘው ከተጨማሪዎች ማብራሪያ ሊጠይቅ ይችላል። ሆኖም የሚጠየቀውና የሚሰጠው ማብራሪያ በሁሉም ተጨማሪዎች እንዲታወቅ በፅሁፍ ሆኖ ተጨማሪዎች ካቀረቡት የመወዳደሪያ ሃሳብ ውስጥ ዋጋውን ወይም የሌሎች መሠረታዊ የሆኑ ነጥቦችን እንዲለወጡ ማለትም በሌሎች ተፎካካሪ አቅራቢዎች ላይ ተፅዕኖ የሚያሳድሩ መሆን የለባቸውም።
- 7.4. በግምገማ ወቅት በነጠላ ዋጋና በጠቅላላ ዋጋ መካከል የዋጋ ልዩነት ቢኖር በነጠላው ዋጋ መሠረት በማስተካከል ይገመገማል።
- 7.5. በግምገማ ወቅት ዋጋው በአኃዝና በፊደል በሚገለጽበት ወቅት ልዩነት ቢኖር በፊደል በተገለጸው መሠረት በማስተካከል ይገመገማል።

8. ጨረታን ውድቅ ስለማድረግ

- 8.1 በጨረታ የተወዳደረው አቅራቢ ግዥ ፈጻሚው መ/ቤት የፈለገውን አነስተኛ የጥራት መመዘኛ መስፈርት ያላሟላ በመሆኑና ብቃት የሌለው ሆኖ ሲገኝ፤
- 8.2 ተጨማሪ በአንዱ ዋጋና በጠቅላላ ዋጋው መካከል የሂሳብ ስህተት ማስተካከያ የማይቀበል ሲሆን፤
- 8.3 ተጨማሪ ያቀረበው የመጨረቻ ሰነድ መሰረታዊ የሆኑ ጉዳዮችን ያላሟላ ሆኖ ሲገኝ፤
- 8.4 በተራ ቁጥር 1.2 የተዘረዘሩትን የጽሁፍ ማስረጃዎች እንዲሁም በተጨማሪ ሌላ ተፈላጊ የሙያ ማረጋገጫ የምስክር ወ/ቀት ተጠይቆ ከጨረታ ማቅረቢያ ሰነዱ ጋር ወይም በበቂ ምክንያት በጨረታ ግምገማ ወቅት ማቅረብ ካልቻለ፤
- 8.5 ተጨማሪዎች የግዥ አካሄዱን ለማዘባት በመመሳጠራቸው በቂ ውድድር አለመደረጉ ሲረጋገጥ፤
- 8.6 የጨረታ ማስከበሪያ ዋስትና ተጠይቆ ያላስያዘ እንደሆነ፤
- 8.7 ተጨማሪዎች ዋጋ አቀራረብ/አሞላል በሚመለከት በተጠየቀው መሰረት ሞልተው ካላቀረቡ።
- 8.8 የአባይ ኮንስትራክሽን ኃ/የተ/የግ/ማህበር የግዥ መመሪያ እና ይህን የጨረታ ሰነድ የሚጥሱ ድርጊቶች መፈፀሙ የተረጋገጠ ከሆነ፤



9. የመጨረቻ ሰነድ ጸንቶ የሚቆይበት ጊዜ

- 9.1 የመጨረቻ ሰነድ እስከ 60 ቀናት ድረስ ፀንቶ ይቆያል።
- 9.2 ግዥ ፈጻሚ መስሪያ ቤት የመጨረቻ ሰነዱ ጸንቶ የሚቆይበትን ጊዜ እንዲራዘምለት ከፈለገ ዕጩ ተወዳዳሪዎችን በጽሁፍ በመጠየቅ ስምምነት ማግኘት አለበት። ሆኖም ዕጩ ተወዳዳሪዎች ካልተስማሙ ያስያዙትን የጨረታ ማስከበሪያ ዋስትና (ቢድ ቦንድ) መውረስ ሳያስፈልግ ከጨረታው ወድድር እንዲሰረዙ ይደረጋል።
- 9.3 የቀረበላቸውን የመጨረቻ ሰነድ የመቆያ ጊዜ ማሻሻያ ጥያቄ የተቀበሉ ተጨማሪዎች መቀበላቸውንና ጊዜውን በመጥቀስ በጽሁፍ ማረጋገጥ ይኖርባቸዋል። በተመሳሳይ ሁኔታ ለዚህ ጨረታ ያስያዙት ዋስትና መቆያ ጊዜ አብሮ እንዲሻሻል ማድረግ ወይም አዲስ ዋስትና ማቅረብ አለባቸው። የጨረታ ዋስትናውን ያላሻሻለ ተጨማሪዎች የጨረታ ሰነዱን ለማሻሻል ፈቃደኛ እንዳልሆነ ተቆጥሮ ከጨረታው ውጭ ይደረጋል።

10. የጨረታ ውጤትን ስለመግለጽና የውል ስምምነት ስለመግባት

- 10.1 ማንኛውም የጨረታ ግምገማ ውጤት በሚመለከታቸው አካላት በጸደቀ በዕለቱ ለተመረጡ በአድራሻቸው በደብዳቤ እና በውስጥ የማስታወቂያ ሰሌዳ የሚገለጹ ሲሆን ላልተመረጡ ተጨማሪዎች ደግሞ በውስጥ የማስታወቂያ ሰሌዳ ያልተመረጡበትን ምክንያት በማካተት በእኩል ጊዜ ለሁሉም ይገለጻል።

- 10.2 አሸናፊው ተጫራች አሸናፊነቱ ከተገለጸለት ቀን ጀምሮ እና የግዥ ውል እንዲፈጽም ከድርጅቱ ደብዳቤ በደረሰው ከ3 የሰራ ቀናት የቅሬታ ጊዜ በኋላ ባሉት 5 የሰራ ቀናት ውስጥ 10% የውል ማስከበሪያ በሲፒአ ወይም በሁኔታ ላይ ያልተመሰረተ የባንክ ዋስትና በማስያዝ የዕቃ አቅርቦት ውል ከግዥ ፈጻሚ መ/ቤት ጋር መፈራረም አለበት።
- 10.3 በጨረታ አሸናፊ የሆነው ተጫራች የአቅርቦት ውል ለመፈረም ፈቃደኛ ካልሆነ ያስያዘውን የጨረታ ማስከበሪያ በመውረስ ከሌሎች ፈቃደኛ ከሆኑ ተጫራቾች ጋር በየደረጃቸው ቅደም ተከተል በአንደኛው ዋጋ ውል በመያዝ እንዲያቀርቡ ማድረግ ይቻላል።

11. የማቅረቢያ ቦታ

- 11.1 የማቅረቢያ ቦታ በውል ጊዜው ባህር ዳር ከተማ ከሚገኘው ከግዥ ፈጻሚው መ/ቤት (አባይ ኮንስትራክሽን ኃ/የተ/የግ/ማህበር) መጋዘን ነው።

12. የውል ማስከበሪያ

- 12.1 አሸናፊ ተጫራቾች ማቅረብ ያለባቸው የውል ማስከበሪያ መጠን ያቀረቡትን ዋጋ 10% የውል ማስከበሪያ (ፐርፎርማንስ ቦንድ) በባንክ በተረጋገጠ ትዕዛዝ /CPO/ ወይም በሁኔታ ላይ ያልተመሰረተ የባንክ ዋስትና (unconditional bank guarantee) ማስያዝ ይኖርባቸዋል።

13. የአቅርቦት መጠን

- 13.1 በጨረታ ሰነዱ ላይ የተጠየቀውን የዕቃ መጠን በውል ወቅት እስከ 20% በመጨመር ወይም በመቀነስ እና አስፈላጊ ሆኖ ሲገኝ ከውል በኋላ እስከ 30% ተጨማሪ የግዥ ትዕዛዝ በመስጠት ግዥ መፈጸም ይቻላል።

14. አቤቱታ ስለማቅረብ


- 14.1 በጨረታ ሂደቱ ጉዳት ወይም ኪሳራ ደርሶብኛል የሚል ወይም በጨረታው ግምገማ ውጤት ቅር የተሰኘ ማንኛውም ተጫራች ጨረታው እንደገና እንዲታይለት የጨረታ ውጤት ከተገለጸበት ቀን ጀምሮ በ3 የሰራ ቀናት ውስጥ አቤቱታውን ለአባይ ኮንስትራክሽን ኃ/የተ/የግ/ማህበር ሥራ አስኪያጅ በጽሁፍ ማቅረብ ይችላል።
- 14.2 አቤቱታ የቀረበበት መ/ቤትም ምላሹን በቀረበለት በ3 የሰራ ቀናት ውስጥ በጽሁፍ ለአቤቱታ አቅራቢው መልስ ይሰጣል።
- 14.3 በድርጅቱ ስራ አስኪያጅ ውሳኔ ያልረካ አቅራቢ በፍርድ ቤት ከስ ሊመሰርት ይችላል።
- 14.4 በተራ ቁጥር 14.1 ከተሰጠው ጊዜ በኋላ የሚቀርብ ማንኛውም አቤቱታ ተቀባይነት አይኖረውም።



የዋጋ መመዘያ ቅጽ

ሎት 01:- ፓምፕ፣ ጀነሬተርና ኤሌክትሮ መካኒካል እቃዎች

ዘንዘልማ ፕሮጀክት

ተ.ቁ	የእቃው አይነት	መለኪያ	ብዛት	የአንዱ ዋጋ ከታክስ ጋር	ጠቅላላ ዋጋ ከታክስ ጋር	ምርመራ
1	 <p>Supply of side suction & side or top discharge multistage, horizontal, surface pump which install @ 1857.15masl with Q=15 l/s, H=32m, duty point NPSHR < 3.5m. motor rated power P2<9.2kw, three phase induction type motor, 380/400v. 50hz, 2900rpm. star delta starting, duty point eff >65%, including appropriate factory assembled control panel board as per the technical specification ,Double flanged GS reducer DN 80 PN 10with one side to fit pump deliveiy flange and GS Double flanged eccentric reducer DN100PN 10with one side to fit pump suction flange all other accessories necessaiy for the complete installation and operation of the pump.</p>	set	2			
2	<p>Supply of open type continuous duty diesel generator set which install @1857.15masl with prime power = 35kva (for 1 duty pump only), three phase, 400V. 50hz. 1500 RPM as per the technical specification, engine & alternator pre-installed on a common rigid frame, switchgear panel, day tank incorporated into the frame, exhaust piping system, including manufacturer working, service& maintenance manual, spare part catalogue and fast moving spare parts like 2 oil filter, 2 fuel filter, 2 air cleaner & standard electrical tool kits 80 pcs and all other accessories necessary for the complete installation atid operation of the generator. 50% of the load</p>	set	1			
3	<p>Volcanizing chemical epoxy with kit which is sufficient for the power cable size (GT 3)</p>	set	1			

4	Flexible Round type copper power cable size 3x25sqmm (rated voltage:Uo/U-0.6/1 kv)	m	105			
5	Flexible Round type copper power cable size 3x35sq.mm) (rated voltage: Uo/U-0.6/1 kv)	m	10			
6	Flexible Round type copper power cable size 3x6sq.mm (rated voltage; Uo/U-0.6/1 kv)	m	60			
7	1 x35 sq.mm earthing cable	M	35			
8	Electric wire 1*1.5mm2	roll	2			
9	Electric wire 1*2.5mm2	roll	1			
10	Flexible electrode connection cable1*1.5mm2	M	350			
11	Earthing copper rods 16 mm2 Length 1.2 m with tape bonding straps	pcs	2			
12	Lightning protection arrestor	Ls	2			
13	Standard coated metal Common Main Distribution Board (CMDDB) which floor standing on concrete seat and lockable door, IP54 or above consisting of: 1 pcs main breaker of MCCB 125A/3ph Icu 25kA, 3 pcs breaker of lighting MCB16A/lp Icu 6kA, 2 pcs breaker of socket MCB 16 A/lp Icu 6kA, 1 pcs lighting surge arrester with load rating, and the board with 25% reserve pitches. Complete with bus bar system of 10A/3p rating , fixing accessories and earthing connection bar terminal,	Ls	1			
14	Standard coated metal Common Main Distribution Board (CMDDB) which floor standing of concrete seat and lockable door, IP54 or above consistins of: 3 pes main breaker of MCCB 25A/3ph Icu.....25kA, 3 pes breaker of lighting MCB 10A/lpIcu.....6kA, 2pcs breaker of socket MCB 10A/lpleu.....6kA, 1 pes lighting surge arrester with load rating, and the board with 25% reserve pitches. Complete with bus bar system of ...A/3p rating , fixing accessories and earthing connection bar tenninal.	Ls	1			



15	A wall mounted standard galvanized metal body & lockable door,4 pole 3 phase Manual Transfer Switch board with 125A rated current capacity	pcs	1			
16	A wall mounted standard galvanized metal body & lockable door.4 pole 3 phase Manual Transfer Switch board with 25A rated current capacity	Pcs	1			
17	Pressure switch, working range of 0-10. bar with 1/2" male socket outlet	Pcs	3			
18	Pressure switch working range of 0-16 bar with 1/2" male socket outlet	Pcs	2			
19	Pressure gauge, glycerin filled 0-16 bar with isolating cock & 1/2" male socket outlet	Pcs	1			
20	Pressure gauge, glycerin filled 0-10 bar with isolating cock & 1/2" male socket outlet	Pcs	1			
21	Permanent electrode 2.5mm diameter	packet	3			
22	Stainless steel cutter disc 180*22.5*1.5 mm	pcs	10			
23	Grinding disc 180*22.5*3mm	pcs	5			
24	Junction box(scatola) size 6*10 cm	PCS	9			
25	Socket outlet	PCS	3			
26	Switch	PCS	3			
27	High insulation nastro	pcs	2			
28	Nastro	pcs	6			
29	Cable trays100mm*50mm*1mm length=3m	pcs	8			
30	Cable lag 25mm ² (ታሳሪ)	pcs	24			
31	Cable lag 35mm ² (ታሳሪ)	pcs	70			
32	Cable lag 6mm ² (ታሳሪ)	pcs	33			
33	Cable tie 500mm*5mm	set	3			
34	Wire 2.5mm ²	m	200			
35	Flixble Copper Cable 1.5mm ²	m	515			
36	Coundit Ø16mm	Pcs	200			
37	Junction box	No	22			



38	Flush mounted Switch	No	6			
39	Flush mounted double Switch	No	5			
40	Fluorescent Lump with holder 36-Watt	No	5			
41	Socket point	No	5			

ግሽ አባይ ፕሮጀክት

ተ.ቁ	የአቃጣይ አይነት	መለኪያ	ብዛት	የአንዱ ዋጋ ከታክስ ጋር	ጠቅላላ ዋጋ ከታክስ ጋር	ምርመራ
1	Supply of Electric submersible pump set which install@1782.7masl wiih a motor of 380V/400V, 50hz impedance type starting, complete with non-return valve, 8" flanged outlet (if the pump outlet is < >8" the reducer must be heavy duty GS), 2pcs level control electrode, factory assemble control panel board as per the technical specification & all other accessories required for installation with Q=28l/s. TDH=199m, motor rated power (P2) <=92kw, pump position=36m below ground (OGL) pump efficiency at duty point >75%, motor and pump over all outside diameter should be <= 192mm (N.B well production casing is 10" steel)	set	1			
2	Volcanizing chemical epoxy with kit which is sufficient for the power cable size G-T5	set	1			
3	Flexible Round type copper power cable size 3x70sqmm (rated voltage:Uo/U-0.6/1 kv)	m	52			
4	Flexible copper cable for electrode connection 1x1.5sqmm	roll	3			

5	Round type copper power cable size 4x70sq.mm (rated voltage: Uo/U-0.6/1 kv)	m	10			
6	cable lag 70mm2 (ታሳሪ)	pcs	22			
7	high insulation nastro	pcs	1			
8	1*35mm2 earthing cable	m	25			
9	earthing road 25mm2 1.2m long	pcs	2			
10	Standard coated metal Common Main Distribution Board (CMDDB) which floor standing on concrete seat and lockable door, IP54 or above consisting of: 1 pcs main breaker of MCCB 250A/3ph Icu 25kA, 3 pcs breaker of lighting MCB16A/lp Icu 6kA, 2 pcs breaker of socket MCB 16 A/lp Icu 6kA, 1 pcs lighting surge arrester with load rating, and the board with 25% reserve pitches. Complete with bus bar system of 10A/3p rating, fixing accessories and earthing connection bar terminal,	Ls	1			
11	A wall mounted standard galvanized metal body & lockable door,4 pole 3 phase Manual Transfer Switch board with 250A rated current capacity	No	1			
12	Junction box(scatola) size 6*10 cm	pcs	10			
13	socket outlet	pcs	3			
14	switch	pcs	3			
15	nastro	pcs	3			
16	2*2.5mm2 power cable	M	20			
17	Cable trays100mm*50mm*1mm length=3m	pcs	4			
18	Cable tie 500mm*6mm	Set	3			
19	Pressure switch, working range of 0-16. bar with isolating cock & 1/2" male socket outlet	No	1			
20	Pressure switch, working range of 0-25. bar with isolating cock & 1/2" male socket outlet	No	1			
21	Pressure Gage working range of 0-25 bar with isolating cock & 1/2" male socket outlet	No	1			



22	permanent electrode 2.5mm diameter	packet	2			
23	stanles steel cutter disc 180*22.5*1.5 mm	pcs	5			
24	grinding disc 180*22.5*3mm	pcs	3			
25	Wire 2.5mm ²	m	160			
26	Wire 1.5mm ²	m	256			
27	Junction box	No	22			
28	Flush mounted Switch	No	7			
29	Flush mounted double Switch	No	5			
30	Fluorescent Lump with holder 36-Watt	No	5			
31	Socket point	No	6			

ሳህላ ፕሮጀክት

ተ.ቁ	የአቃዉ አይነት	መለኪያ	ብዛት	የአንዱ ዋጋ ከታክስ ጋር	ጠቅላላ ዋጋ ከታክስ ጋር	ምርመራ
1	Electric slurry submersible raw water /Dewatering pump with appropriate cooling sleeve and motor of 380V/400V, 50hz impedance type or equivalent starting type complete with non-return valve, 3" threaded pump outlet(if the pump outlet is< or> 3" the reducer must be medium duty GS) including level sensors control electrode (3) for each board and appropriate factory assmbled control panel board with Q=9.8L/s, H=52m, pump power ≤9.2kw, 2900 rpm ,pump efficiency at duty point should be ≥ 65%.maximum pump with motor length including cooling sleeve should be < 3.5m	Set	2			



2	Multi stage centrifugal side or end suction & radial or side discharge surface pump (1+1), with Q=9.8l/s, TDH=149m, Pump power ≤26kw, pump efficiency at duty point ≥65%, 3phase, squirrel cage, induction type, 380/400v, 50hz concentric reducer DN80 PN10 to fit pump delivery side and eccentric reducer DN 100 PN 10 to fit pump suction side including Pump manufacturer starting control panel board, and all other accessories necessary for the complete Installation and operation manual of the pump. NPSHR <6.6m(@booster)	Set	2			
3	flexible copper wire size 1x1.5mm ² (1 roll=100mtr)	roll	4			
4	Diesel generator set, continuous rating, as per the technical specification, engine & alternator pre-installed on a common rigid frame, switchgear panel, day tank incorporated into the frame, exhaust piping system, including manufacturer working, service & maintenance manual, spare part catalogue(2 pcs fuel and 2 pcs oil filter, 2 pcs air cleaner, belt, electrical and mechanical toolkit 80 pcs) and all accessories required for Installation with prime power =85KVA, three phase, 400V, 50hz,	set	1			
5	Continuous duty diesel generator set which with prime power =7.5 KVA, three phase, 400V, 50hz, 1500 RPM as per the technical specification, engine & alternator pre-installed on a common rigid frame, switchgear panel, day tank incorporated into the frame, exhaust piping system, including manufacturer working, service maintenance manual, spare part catalogue and fast-moving spare parts like oil filter, fuel filter, air cleaner, AVR, Belt and standard electrical tool kits	Set	1			
6	flat or round type flexible Copper power cable size 4x4mm ²	mtr	40			
7	flat or round type flexible Copper power cable size 4x10mm ²	mtr	40			
8	flat or round type flexible Copper power cable size 4x16mm ²	mtr	150			



9	flat or round type flexible Copper power cable size 4x25mm ²	mtr	35			
10	GT-3 vulcanizing kit with chemical epoxy	set	1			
11	A wall mounted 4 poles 3phase Circuit breaker 150A/3ph rated current, standard coated metal body & lockable door.	set	2			
12	A wall mounted 4 poles Manual Transfer Switch board with 160A/3ph rated current, standard coated metal body & lockable door.	set	1			
13	Standard coated metal Common Main Distribution Board (CMDDB) which wall mounted lockable door, IP44 consisting of:					
14	2 pcs main breaker 20A/3phase					
15	1 pcs breaker of MCB 16A/1 ph Icu..... 3kA					
16	1 pcs breaker of lighting MCB 10A/1p Icu.... 3kA					
17	and the board with 25% reserve pitches, complete with bus bar system of 20A/3p rating, fixing accessories and earthing connection bar terminal.	set	1			
18	Standard coated metal Common Main Distribution Board (CMDDB) which wall mounted lockable door, IP44 consisting of:					
19	2 pcs main breaker 63A/3phase					
20	1 pcs breaker of MCB 16A/1ph Icu.... 3kA					
21	1 pcs breaker of lighting MCB 10A/1p Icu.... 3kA					
22	and the board with 25% reserve pitches, complete with bus bar system of 20A/3p rating, fixing accessories and earthing connection bar terminal.	set	1			
23	Standard wall mounted lockable door sub-Distribution Board (SDB-B) with IP44 consisting of:					
24	1 pcs Sub-main breaker of MCB 16A/1ph Icu... 3kA					
25	1 pcs breaker of lighting MCB 10A/1p Icu.... 3kA					
26	and the board with 25% reserve pitches, complete with bus bar system of 20A/1p rating, fixing accessories and earthing connection bar terminal.	set	1			
27	wire conductor of 2.5mm ²	roll	6			



28	junction boxes Ø65mm with cover	pcs	36			
29	10A/1p Standard ON/OFF single pole switches	No	24			
30	10A/1p Legrand mosaic type two-circuit switches	No	3			
31	lighting fixture 11w LED lump	No	27			
32	Wall mounted lighting fixture with compact florescent lamp and water proof RZB IP56 type	No	9			
33	Wall mounted lighting fixture with compact florescent lamp and Massive 32003/11/10 IP44 type	No	6			
34	16A/1P LEGRAND mosaic type water proof socket outlets with ground contact	No	12			
35	flexible Round type copper power cable size 3x4sq.mm (rated voltage: Uo/U-0.6/1kv)	mtr	150			
36	Octagonal (Imported type) Galvanized 3m steel lighting pole with dia.100mm at base, dia. 60mm at top, 3mm thickness throughout its length, erection concrete with base plate (in drawing) and water proof free fixed door for terminal box, including insulated clamp for fuse holder, 3x2.5mm ² cable wiring through flexible pvc conduit inside pole, protective fuse holder with 4A fuse, 80w sodium lamp with IP56 and electronic ballast lamp holder and all as specified in the drawing.	No	3			
37	earthing copper road with 50mm ² c.s area 1.5m length	pcs	3			
38	earthing cable 1*50mm ²	M	50			
39	earthing cable 1*6mm ²	M	15			
40	earthing cable 1*4mm ²	M	15			
41	lighting protection araster	pcs	2			
42	cable try 100*50 mm and 3m length	pcs	10			
43	cable tie 500mm ,6mm	packet	5			
44	cable luge ታሳሪ 25 mm ²	pcs	32			
45	cable luge ታሳሪ 16 mm ²	pcs	20			
46	cable luge ታሳሪ 4 mm ²	pcs	21			
47	permanenet electrode 2.5mm	packet	4			



48	cutter disc 180*22.5*1.5 mm	pcs	24			
49	grinding disc 180*22.5*3.5 mm	pcs	11			
50	Nastro	pcs	18			
51	high insulation Nastro	pcs	2			
52	Standard wall mounted lockable door sub-Distribution Board (SDB-B) with IP44 consisting of:					
53	1 pcs Sub-main breaker of MCB 16A/1ph Icu..... 3kA					
54	and the board with 25% reserve pitches, Complete with bus bar system of 20A/1p rating, fixing accessories and earthing connection bar terminal.	set	1			
55	Octagonal (Imported type) Galvanized 3m steel lighting pole with dia.100mm at base, dia. 60mm at top, 3mm thickness throughout its length, erection concrete with base plate (in drawing) and water proof free fixed door for terminal box, including insulated clamp for fuse holder, 3x2.5mm ² cable wiring through flexible pvc conduit inside pole, protective fuse holder with 4A fuse, 80w sodium lamp with IP56 and electronic ballast lamp holder and all as specified in the drawing.	No	3			



ሎት 02:- ፓይፕ እና የወሃ እቃዎች

ሳህ ፕሮጀክት

ተ.ቁ	የእቃው አይነት	መለኪያ	ብዛት	የአንዱ ዋጋ ከታክስ ጋር	ጠቅላላ ዋጋ ከታክስ ጋር	ምርመራ
-----	-----------	------	-----	-----------------	-----------------	------

1	GI pipe light class 2" length 6m	pcs	3			
2	3" Gs medium class pipe length 6m	pcs	1			
3	4" Gs medium class pipe length 6m	pcs	2			
4	6" threaded Gs medium class pipe length 6m	pcs	8			
5	6" bedded midium class type socket coupling	pcs	2			
6	blue paint for steel	galon	1			
7	DN 80 flange pn 10	pcs	2			
8	DN 80 flange pn 16	pcs	1			
9	DN 100 flange pn10	pcs	7			
10	DN 100 flange pn16	pcs	6			
11	DN 150 flange pn 10	PCS	27			
12	DN 150 flange pn 10 blind	PCS	3			
13	DN 80 flate gasket PN16	PCS	8			
14	DN 80 flate gasket PN10	PCS	7			
15	DN 100 flate gasket PN10	PCS	13			
16	DN 100 flate gasket PN16	PCS	12			
17	DN 150 flate gasket PN 10	PCS	52			
18	M8 *60*1.15 MM nut bolt with washer	PCS	4			
19	M12 *1200 * 1.15 MM anchor bolt	pcs	20			
20	M16 * 100*1.15 MM nut and bolt with washer	pcs	316			
21	M20 *120*1.15 MM nut and bolt with washer	PCS	480			
22	GS double flanged 90 degree elbow DN 80 pn 16	PCS	1			
23	GS double flanged 90 degree elbow DN 100 pn 10	PCS	2			
24	GS double flanged 90 degree elbow DN 150 pn 10	PCS	7			
25	CI double flanged water meter DN150mm PN10	PCS	1			
26	CI double flanged gate valve, DN150mm PN10	PCS	4			
27	CI double flanged gate valve, DN100mm PN10	PCS	2			
28	CI double flanged gate valve, DN100 PN16	PCS	1			
29	CI double flanged gate valve, DN80 PN10	PCS	1			
30	CI double flanged gate valve, DN80 PN16	PCS	1			
31	CI double flanged check valve DN80 mm, PN16	PCS	2			



32	CI double flanged check valve DN100 mm, PN16	PCS	1			
33	CI double flanged check valve DN150 mm, PN10	PCS	3			
34	Pressure gauge, glycerine filled 0-10 bar with isolating cock & 1/2" male socket outlet	PCS	1			
35	Pressure gauge, glycerine filled 0-16 bar with isolating cock & 1/2" male socket outlet	PCS	1			
36	Pressure switch with 1/2" male socket, 0-16 bar with isolating cock & 1/2" male socket outlet	PCS	1			
37	CI double flanged dismantling joint, DN80, PN16	PCS	2			
38	CI double flanged dismantling joint, DN100, PN10	PCS	2			
39	CI double flanged dismantling joint, DN150, PN10	PCS	4			
40	GS double flanged Reduced Tee DN 100 /80/100 PN PN16	PCS	2			
41	GS double flanged Tee, DN150/80/150 PN10	PCS	4			
42	GS Double flanged 90-degree elbow, DN80, PN10	PCS	1			
43	CI double flanged orifice air release valve, DN80 PN10	PCS	3			
44	CI double flanged orifice air release valve, DN80 PN16	PCS	1			
45	CI double flanged strainer DN150, PN10	PCS	1			

ግሽ አባይ ፕሮጀክት

ተ.ቁ	የአቃው አይነት	መለኪያ	ብዛት	የአንዱ ዋጋ ከታክስ ጋር	ጠቅላላ ዋጋ ከታክስ ጋር	ምርመራ
1	GS flange DN50 PN16	pcs	2			
2	GS flange DN100 PN16	pcs	17			
3	GS blind flange DN100PN 10	pcs	4			
4	2" GS medium class pipe	M	14			
5	3" GS havey class pipe	M	6			
6	3" GS medium class pipe	M	17			
7	4" GS medium class pipe	M	131			
8	4" GS heavy class pipe	M	6			
9	4" GS medium embedded type coupling	pcs	19			
10	Double flanged Dismantling joint, DN80 PN10	PCS	3			



11	Double flanged Dismantling joint, DN100 PN10/16	PCS	5			
12	Double flanged turbine type water meter DN 80 PN 10	PCS	1			
13	Flanged Woltman water meter turbine type, DN 100mm PN16	PCS	1			
14	Double flanged check valve DN 80PN10	PCS	3			
15	Double flanged Non-return valve (check valve), DN100.mm, PN16	PCS	1			
16	GS reducer tee DN80/50/80 PN10	PCS	1			
17	Double flanged GS Tee. DN 100./50./100PN16	PCS	3			
18	Double orifice Flanged Air release valve DN 50 PN10/16	PCS	2			
19	Double Flanged Gate valve, DN100mm PN10/16	PCS	4			
20	GS Double flanged eccentric reducer, DN100PN 10	PCS	2			
21	Flanged stainless steel strainer DN 100PN 10	PCS	1			
22	GI equal Cross Tee 3/4" medium class	NO	2			
23	Faucet 3/4"	NO	6			
24	GS Flanged DN 65mm Gate Valve, PN10	NO	1			
25	GS Flanged DN 40MM Gate Valve, PN10	NO	1			
26	1 1/4" Gate Valve, medium class PN10	NO	2			
27	GI 1 1/4" Water Meter, medium class PN10	NO	1			
28	GI Medium class 1 1/4" Nipple	NO	6			
29	GI Medium class 3/4" Nipple	NO	4			
30	GI threaded 90 degree elbow 1 1/4", 90° medium class	NO	5			
31	GI 1 1/4", Union Medium class	NO	1			
32	GI equal tee 1 1/4", medium class	NO	1			
33	Double Socket Reducer 1 1/4"*3/4"	NO	2			
34	Coupling /Socket 3/4"		6			
35	GS Flanged Gate valve, DN80 PN10	NO	4			
36	Flanged Single Orifice air release valve, DN50 PN16	NO	1			
37	Flanged Gate valve, DN50 PN16	NO	6			
38	Double flanged CI Gate Valve DN150/6", PN16	NO	2			
39	Double flanged CI Gate Valve DN250, PN16	NO	1			
40	Flanged Reducer Tee DCI DN300*150*300, PNO	NO	1			
41	Flanged Reducer Tee DCI DN300*250*300, PN10	NO	1			



42	Flanged Reducer DCI DN300*200, PN10	NO	1		
43	Flanged Elbow DCI DN250, PN10	NO	1		
44	Flanged Reducer Tee DCI DN150*100*150, PNO	NO	1		
45	HDPE Compression Female Adapter OD40/DN11/4", PN10	NO	4		
46	HDPE Compression Equal Tee OD40*40*40, PN10	Pcs	1		
47	HDPE Compression Reducer OD63/40, PN10	Pcs	1		
48	HDPE Butt weld Reducer OD110/63, PN10	Pcs	1		
49	HDPE Butt weld Reducer Tee OD160*110*160, PN10	Pcs	1		
50	HDPE Butt weld Reducer OD160/90, PN10	pcs	1		
51	HDPE Butt weld Reducer OD110/75, PN10	No	1		
52	HDPE Butt weld Reducer Tee OD75*50*75, PN10	No	1		
53	3" Bedded type Ring Coupling	No	2		
54	DN 80 flange pn 10 GI	No	9		
55	Medium class GS 11/4" Pipe	m	8		
56	GS 3/4" Pipe	m	6		
57	DCI DN250, PN10	pcs	19		
58	HDPE Pipe OD160, PN10	m	32		
59	HDPE Pipe OD40, PN10	m	44		
60	HDPE Pipe OD63, PN10	m	3,121		
61	HDPE Pipe OD180, PN10	m	3,030		
62	HDPE Butt weld Reducer OD180/110, PN16	pcs	3		
63	HDPE stubflanged adaptor with backring OD280, PN10	pcs	1		
64	HDPE stubflanged adaptor with backring OD180/8", PN10	pcs	1		
65	HDPE stubflanged adaptor with backring OD110/4", PN10	pcs	4		
66	HDPE stubflanged adaptor with backring OD63, PN10	pcs	1		
67	HDPE stubflanged adaptor with backring OD90, PN10		2		
68	HDPE stubflanged adaptor with backring OD75, PN10		2		
69	HDPE stubflanged adaptor with backring OD50, PN10		2		
70	HDPE OD180 Butt weld 90°-Elbow, PN10	Pcs	6		
71	DN150 CI double flanged 90-degree bend, pn10	Pcs	2		



72	Nut and Bolt with washier M-20 (#30) where the length is equal to or greater than 130mm	No	236			
73	Nut and Bolt with washier M-16 (#24) where the length is equal to or greater than 130mm	No	404			
74	Nut and Bolt with washier M-14 (#22) where the length is equal to or greater than 130mm	No	168			
75	Flat Gasket DN180mm, PN10	Pcs	2			
76	Flat Gasket DN100mm, PN10/16	Pcs	40			
77	Flat Gasket DN80mm, PN10/16	Pcs	27			
78	Flat Gasket DN65mm, PN10	Pcs	4			
79	DN 50 flate gasket PN10/16	Pcs	16			
80	Flat Gasket DN150mm, PN10	Pcs	7			
81	Flat Gasket DN200mm, PN10	Pcs	4			
82	Flat Gasket DN250mm, PN10	Pcs	3			
83	Flat Gasket DN280mm, PN10	Pcs	1			
84	Flat Gasket DN300mm, PN10	Pcs	6			
85	O-Ring Gasket DN250mm, PN16	Pcs	21			



ዘንዘል ጥርጅክት

ተ.ቁ	የእቃው አይነት	መለኪያ	ብዛት	የአንዱ ዋጋ ከታክስ ጋር	ጠቅላላ ዋጋ ከታክስ ጋር	ምርመራ
1	20mm GS Well head cover 16." flange, with internal DN 135mm hole	No	1			
2	fanged Adaptor DN150 PN 25	No	9			
3	fange DN80 PN 25	No	2			
4	heavey class 5" pipe	m	42			
5	heavey class 6" pipe	m	3			
6	medium class 6" pipe	m	4			
7	DN 125 PN 25 flange	Pcs	28			
8	Double flanged GS Elbow 90 degree DN 150 PN 25	Pcs	3			
9	Double flanged Dismantling joint, DN150 PN25	Pcs	2			
10	Flanged Woltman water meter DN 150mm PN25	Pcs	1			

11	Double flanged check valve, DN150.mm, PN25	Pcs	1			
12	Double flanged GS Tee.DN 150./80./150PN25	Pcs	2			
13	Double Flanged Gate valve, DN150mm PN25	Pcs	1			
14	Double Flanged Gate valve for wash out, DN80.mm PN25	Pcs	1			
15	Pipe supports as per the engineer order either piped or reinforced concrete type	Pcs	3			
16	Single flanged GS elbow DN80 PN 25	Pcs	1			
17	Double flanged GS reducer DN 200/100 PN10	Pcs	1			
18	DCI DN300 pipe	pcs	38			
19	HDPE OD200, PN16	m	210			
20	HDPE OD250, PN20	m	908			
21	HDPE Butt weld Reducer OD250/160, PN16	pcs	1			
22	HDPE Butt weld Reducer OD250/200, PN20	pcs	1			
23	HDPE stubflanged adaptor with backring OD160/6", PN16	pcs	1			
24	HDPE stubflanged adaptor with backring OD200/8", PN16/20	pcs	8			
25	DCI Flanged Tee DN200*80*200, PN16	Pcs	6			
26	DCI Flanged Tee DN200*100*200, PN20	Pcs	1			
27	Air Release valve Single orifice DN80, PN16	Pcs	2			
28	Air Release valve Double orifice DN80, PN20	Pcs	2			
29	GI Flanged gate valve DN100, PN20	Pcs	1			
30	Single Flanged GS pipe DN100, PN20 L=2m	Pcs	1			
31	Nut and Bolt with washier #30	No	696			
32	Nut and Bolt with washier #24	No	160			
33	O-Ring Gasket DN300mm, PN16	Pcs	38			
34	Flat Gasket DN200mm, PN16/20	Pcs	24			
35	Flat Gasket DN150mm, PN16/25	Pcs	19			
36	Flat Gasket DN125mm, PN25	Pcs	15			
37	Flat Gasket DN100mm	Pcs	5			
38	Flat Gasket DN80mm	Pcs	15			



ደንብ ፕሮጀክት

ተ.ቁ	የእቃው አይነት	መለኪያ	ብዛት	የአንዱ ዋጋ ከታክስ ጋር	ጠቅላላ ዋጋ ከታክስ ጋር	ምርመራ
1	HDPE Butt weld Reducer Tee 315x125x315mm PN 10,PE100 .	PCS	15			
2	Double flanged Gs gate valve dia, 110mm PN 10 compatible to HDPE Pipe with dia. Of 125mm	PCS	15			
3	HDPE butt weld flanged long spigot /adapter 125mm	PCS	15			
4	Compression HDPE male adapter 110*4" Pn 10 PE 100	PCS	30			
ሳምባ ፕሮጀክት						
ተ.ቁ	የእቃው አይነት	መለኪያ	ብዛት	የአንዱ ዋጋ ከታክስ ጋር	ጠቅላላ ዋጋ ከታክስ ጋር	ምርመራ
1	HDPE pipe PE 100 OD 280 mm,PE 100 PN 6	Meter	2400			
2	DCI Double Orifice Air Release Valve DN80 PN25	pcs	1			
ሱሲ ፕሮጀክት						
ተ.ቁ	የእቃው አይነት	መለኪያ	ብዛት	የአንዱ ዋጋ ከታክስ ጋር	ጠቅላላ ዋጋ ከታክስ ጋር	ምርመራ
1	HDPE pipe PE 100 OD 250mm PN10	Meter	891			
2	HDPE pipe PE 100 OD 140mm PN10	Meter	242			
3	geomebrane 1.5mm thick	m2	3710			



ሎት 03:- የኮንስትራክሽን እቃዎች

ዘንዘልማ ፕሮጀክት

ተ.ቁ	የእቃው አይነት	መለኪያ	ብዛት	የአንዱ ዋጋ ከታክስ ጋር	ጠቅላላ ዋጋ ከታክስ ጋር	ምርመራ
1	Timber 20cm width	pcs	15			
2	Timber (Australia) 25cm width	pcs	10			
3	Chipwood 8mm thick smooth surface 2.40*1.20	pcs	10			
4	Nails no 4	packet	2			
5	Nails no 6	packet	7			
6	Nails no 8	packet	10			
7	Nails no 9	packet	10			
8	Nails no 10	packet	15			
9	Nails no 12	packet	10			
10	Roofing nail	packet	2			
11	Cis G-32	pcs	20			
12	Cis G-28	pcs	30			
13	Galvanized metal sheet G-32	m	11			
14	Reinforcement bar 8mm diameter length 12mm 4.737kg/berga	berga	72			
15	Reinforcement bar 10mm diameter length 12mm 7.401kg/berga	berga	18			
16	Reinforcement bar 12mm diameter length 12mm 10.658kg/berga	berga	198			
17	Black wire 2.5mm thick flexible type	kg	35			
18	Water proof wall paint 4litter/gallon	gallon	7			
19	Morale 7*5 Australia	pcs	18			
20	Morale 4*5 Australia	pcs	19			
21	Angle iron 50*50*3mm	pcs	19			
22	Barbed wire 8kg 2.5mm thick	roll	9			
ግዥ አባይ ፕሮጀክት						



ተ.ቁ	የአቃጣይ አይነት	መለኪያ	ብዛት	የአንድ ዋጋ ከታክስ ጋር	ጠቅላላ ዋጋ ከታክስ ጋር	ምርመራ
1	Timber 400cm*20cm/2.5cm Australia	pcs	15			
2	Timber 400cm*25cm/2.5cm Australia	pcs	10			
3	Nails no 12	packet	11			
4	Nails no 10	packet	10			
5	Nails no 9	packet	7			
6	Nails no 8	packet	10			
7	Nails no 4	packet	2			
8	Roofing Nails	packet	3			
9	Corrugated Iron sheet (CIS) G-32 4kg/sheet 0.25mm thick	pcs	18			
10	Corrugated Iron sheet (CIS) G-28 6kg/sheet 0.40mm thick	pcs	30			
11	Flat/Plain sheet metal G-28 Galvanized rolled and 0.40mm thick	m	11			
12	Reinforcement bar 6mm dia	kilogram	50			
13	Reinforcement bar 8mm diameter length 12mm 4.737kg/berga	berga	34			
14	Reinforcement bar 10mm diameter length 12mm 7.401kg/berga	berga	19			
15	Reinforcement bar 12mm diameter length 12mm 10.658kg/berga	berga	65			
16	Black wire 1.5mm thick flexible type	kg	25			
17	Zigeba/tside purlin 4*5cm L=4m የሀገር ዉስጥ	pcs	19			
18	Zigeba purlin 7*5cm L=4m Australia	pcs	18			
19	Chipwood 8mm thick smooth surface 2.40*1.20	pcs	10			
20	Angle iron 50*50*3mm L=6m	pcs	10			
21	Angle iron 50*50*5mm L=6mm	pcs	19			
22	Galvanized Barbed wire 2.5mm thick with 8kg/roll L=80m	roll	14			



23	SHS 100mm*100mm*4mm L=6m	pcs	2			
24	SHS 80mm*80mm*3mm L=6m	pcs	2			
25	Water proof wall paint 4litter/gallon	gallon	9			
26	Fiber/ቃጫ	kg	2			
27	Anti rust paint	gallon	3			

ሳምባ ፕሮጀክት

ተ.ቁ	የአቃጫ አይነት	መለኪያ	ብዛት	የአንዱ ዋጋ ከታክስ ጋር	ጠቅላላ ዋጋ ከታክስ ጋር	ምርመራ
1	Gabion Box 1.5x1x1mm Size 1.5m*1m*1m, 13kg/Pcs, 8cm*10cm hole diameter, mesh wire with 2.5mm dia., zinc coated galvanized wire, Boulder Φ 3mm and Triple Twisted hexagonal woven wire mesh	pcs	40			



ሎት 04:- የነዳጅ ቦታ ኪራይ አገልግሎት ግዥ

ተ.ቁ	የጭነቱ ዓይነት	መነሻ	መድረሻ	መለኪያ	ብዛት	የአንድ ትሪፕ የኪራይ ዋጋ
1	ናፍጣ (የቦታ የመያዝ አቅም 45000 እና በላይ)	ጅቡቲ	ርብ መስኖ ፕሮጀክት	ትሪፕ	8	

ጠቅላላ ዋጋ	
ምርመራ	

